

Storm iCLASS Keypad Reader

Part Code: HID-S40

(Metal Keys)



HID-S40i

(Illuminated Polymer Keys)



The HID-S40 and HID-S40i are robust readers with integral keypad, designed for both indoor and outdoor applications, where Two Factor Authentication is required.

Featuring genuine HID® iCLASS SE®, Seos®, contactless technology, these Keypad Readers offer enhanced security by dual authentication. Authorised access through a secured door or barrier can be gained by entry of a valid PIN and presentation of an authorised 13.56 MHz contactless card, token or Seos® compatible NFC device.

Features and Benefits

- Two Factor Authentication
- Bi-colour LED and buzzer for user feedback
- Moving tactile keytops with home key tactile idents, ensure accessibility for those with sensory impairment
- Metal keys for maximum robustness (HID-S40)
- Illuminated polymer keys for low light applications (HID-S40i)
- Dimensions: 100mm x 119mm x 43mm

Technical

- Supports multiple technologies including iCLASS SE® Seos®, standard iCLASS®, MIFARE™, and MIFARE DESFire™
- Frequency: 13.56MHZ
- Wiegand Interface
- HID-S40: 5Vdc or 12Vdc at 200mA max
- HID-S40i: 12Vdc at 250mA max
- Read Range: Up to 100mm
- Operating temperature: -35 °C to +65 °C
- Operating humidity: 5% to 95% non-condensing
- 1 Year Warranty

www.controlsoft.com

© 2015 Controlsoft Limited. All rights reserved. Controlsoft and the Controlsoft logo are registered trademarks of Controlsoft Limited in Europe, the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

